least 30.

24. (New) The absorbent insert according to Claim 22, wherein the absorbent polymer has a retention of at least 25 g/g.

25. (New) The absorbent insert according to Claim 22, wherein the absorbent polymer has an absorption under pressure of at least 15 g/g.

- 26. (New) The absorbent insert according to Claim 22, wherein the soluble ratio of the absorbent polymer is 3.5 wt.-%.
- 27. (New) The absorbent insert according to Claim 22, wherein having a migration value of ≤ 15 mg/g.
- 28. (New) The absorbent insert according to Claims 22, wherein the top and bottom covering layer comprise a plastic or cellulose film, a fabric or a fleece; and

at least one part of the covering layer film is permeable to water or an aqueous liquid as a result of a perforation.

29. (New) Absorbent insert according to Claim 22, wherein the core comprises fleece, a fiber, a fabric;

wherein the polymer absorbing an aqueous liquid is dispersed and optionally fixed.

- 30. (New) Absorbent insert according to Claim 29, wherein the core has an arrangement in layers of the absorbent polymer part within the core of fiber and fabric.
- 31. (New) Absorbent insert according to Claim 29 or 30, wherein the fiber is a hollow fiber.
- 32. (New) Absorbent insert according to Claim 22, wherein the absorbent polymer is made from a partially neutralized monoethylenically unsaturated monomer containing an acid group and, optionally another monomer copolymerizable therewith:

-2-

wherein the absorbent polymer is further made from crosslinker as well as a polymer